## **Product Specification**

**Small Batch Sieving** 

# 200-S

A 200mm diameter vibratory sieve designed to sit directly on top of a container.

A circular frame supports the sieve and allows ingredients to be tipped into the top and check sieved into a container below.

The Sievmaster 200-S can be used for straining liquids as well as dry ingredients. Different mesh screens for coarse, medium, & fine/liquid applications are available.

#### Features & Benefits

- Easy-Clean hygienic design, no crevices
- Conforms to CE, UKCA, FDA, and EC 1935/2004 regulations.
- No tool, quick change screens
- Wet or dry applications
- 0.05 kW (0.1 HP) vibratory motor

- Dust and waterproof to at least IP65
- Open top hopper for ease of dispensing
- All stainless steel body and contact parts
- Low maintenance/running costs tool free disassembly & minimal servicing

## Industries:









#### **Product Options\***

**Top Dust Cover** removable top cover with gasket and clamp.

**Bench Mounting Kit -** allows the sieve to be free-standing.

\*More options available on request



**Top Cone Meshed -**Food grade adhesive.

wheels available.





## **Typical Materials**

 Most food, beverage, chemical powders and granular products

by farleygreene

mas

d

• Liquid separation



• Internal Dull Polish to <0.8 Ra



	<		۵			O			)								
9	AN SIEVE				SM200-S (mm) 545	300	250	150	200mm t @ 355mm from ground	SM200-S	110 / 240	50 / 60 hz	45 W	1	Q		ALL DIMS. ARE APPROX. NOT TO BE USED FOR FINAL PLANNING. FULL DRAWINGS CAN BE SUPPLIED ON REQUEST. SUBJECT TO CHANGE AT ANY TIME.
5	SM 200-S ARTISAN SIEVE			-	DIMENSION	( Ω	υ	Q	Screen diameter = 200mm Bench mount legs give outlet height @ 355mm from ground	ELECTRICAL	Voltage	Frequency	Power	Phase	ATEX		E USED FOR FINAL PLANNING. FULL DRAWINGS
4			¥Ø				-1		Bench		2			-1			ALL DIMS. ARE APPROX. NOT TO BE
e						0		Ĩ				R				Ŧ	
2					F	$\int$		- ⊘B									
1															_		

Copyright © 2025 Issue C 04.25